

NOMENCLATURE & ORDERING GUIDE

Model: RW - 01 - 20 - 70 - 100 - 3 - 1.1 - x - C - I

Rainwater System

System Supply

- 01: Irrigation
- 02: Toilets
- 03: Irrigation & Toilets

Supply Flow Rate

- 10: 10 GPM
- 20: 20 GPM
- 30: 30 GPM
- 40: 40 GPM
- 50: 50 GPM
- 60: 60 GPM
- 70: 70 GPM

Supply Pressure

- 50: 50 psi
- 60: 60 psi
- 70: 70 psi
- 80: 80 psi
- 90: 90 psi
- 100: 100 psi

Filtration Size

- 100: 100 micron
- 50: 50 micron
- 5: 5 micron
- 1: 1 micron

Backup Supply

- I: Indirect through air-gap
- D: Direct through backflow preventer

Pump Type

- C: Mounted on skid
- S: Submersible

Disinfection

- x: no disinfection
- U: UV light
- C: Chlorine
- UC: UV light & chlorine

Day Tank Size

- X: no day tank
- 0.5: 550 gallons
- 1.1: 1,100 gallons
- 1.5: 1,500 gallons
- 2.0: 2,000 gallons

Electrical Service

- 1: 115V
- 2: 115V + 230V single phase
- 3: 208 - 230V three phase
- 4: 460V three phase